

Product datasheet

Specifications



APC Smart-UPS C, Line Interactive, 2000VA, Tower, 230V, 6x IEC C13+1x IEC C19 outlets, USB and Serial communication, AVR, Graphic LCD

SMC2000I

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead Time Usually Ships within 2 Weeks

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Rated Power In W 1300 W

Rated Power In Va 2000 VA

Product Or Component Type Uninterruptible power supply (UPS)

Input Connection Type IEC 320 C20

Output Connection Type 6 IEC 320 C13
1 IEC 320 C19

Number Of Rack Unit 0U

Battery Type Lead-acid battery

Provided Equipment CD with software
Documentation CD
USB cable

Batteries & Runtime

Run Time [View Runtime Graph](#)

Extended Runtime 0

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 3 h

Number Of Battery Replacement Quantity 1

Battery Life 3...5 year(s)

Replacement Battery [APCRBC148](#)

Battery Charger Power 166 W rated

General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	Entry level
Redundant	No

Physical

Colour	Black
Height	21.6 cm
Width	17 cm
Depth	44 cm
Net Weight	27.5 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes

Input

Input Voltage Limits	170...300 V adjustable 180...287 V
Network Frequency	47...63 Hz

Output

Harmonic Distortion	Less than 5 % at full load
Maximum Configurable Power In Va	2000 VA
Maximum Configurable Power In W	1300 W
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50 Hz sync to mains

Conformance

Product Certifications	C-Tick CE EAC GOST SABS VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic Level	45 dBA
Heat Dissipation	135 Btu/h
Operating Altitude	0...10000 ft

Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control Panel	Multifunction LCD status and control console
Free Slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rate	300 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	33 cm
Package 1 Width	59 cm
Package 1 Length	37 cm
Package 1 Weight	30 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)
