

Product datasheet

Specifications



APC Easy UPS, 900VA, Tower, 230V, 2 Universal + 1 IEC C13 outlets, AVR

BVX900LI-MS

Overview

Lead Time Usually in Stock

Main

Main Input Voltage 230 V AC 1 phase

Main Output Voltage 230 V AC 1 phase

Rated Power In W 480 W

Rated Power In Va 900 VA

Input Connection Type IEC 60320 C14

Output Connection Type 2 universal
1 IEC 60320 C13

Cable Length 1.22 m

Number Of Cables 1

Battery Type Lead-acid battery

Provided Equipment User manual

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 8 h

Battery Voltage 12 V

Battery Capacity 9.0 Ah

Battery Life 2...3 year(s)

Replacement Battery [RBC17](#)

Extended Runtime 0

General

Max Runtime 120 min

Number Of Power Module Free Slots 0

Number Of Power Module Filled Slots 0

Redundant No

Ups Size	WS
----------	----

Physical

Colour	Black
Height	16 cm
Width	12 cm
Depth	35.5 cm
Net Weight	6 kg
Mounting Support	Floor
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
Input Voltage Limits	140...300 V 230 V AC
Cos Phi	0.53

Output

Maximum Configurable Power In W	480 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	00:01:00 480 W
Graph Display	1
Half Load Runtime	00:06:30 240 W
Maximum Configurable Power In Va	900 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 50000 euros

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing

Storage Altitude	0...3000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

Surge Protection and Filtering

Surge Energy Rate	273 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	25 cm
Package 1 Width	43 cm
Package 1 Length	19.7 cm
Package 1 Weight	6.5 kg
Scc14	10731304404368

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

- Toxic Heavy Metal Free
- Mercury Free
- Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information