

DELL27USB-C MONITOR **S2723HC**



THE WORLD'S # 1 MONITOR COMPANY*

*Source: IDC Worldwide Quarterly PC Monitor Tracker (Q3 2021)

DELL MONITORS-S-series

Simplified for greater space

27" monitor with the USB-C single-cable solution designed to keep your desktop clutter-free. Featuring built-in speakers and In-Plane Switching (IPS) technology.



Stunning, minimalist design

The new micro-texture design compliments every home office with its platinum silver pattern. Designed with 3-sided ultrathin bezel that provides flawless continuity.

Enhanced experience

Get superb clarity on a 27" FHD monitor with 99% sRGB color coverage and In-Plane-Switching (IPS) technology for rich color across a wide viewing angle. Includes dual 3W built-in speakers for an engaging audio experience. Dell's TÜV-certified ComfortView Plus feature



Clutter-free connectivity

The single-cable USB-C solution combines 65W power delivery with video, audio and data transmission in one cable creating more desk space for what's important.



DELL MONITORS-S-series

27" FHD monitor with USB-C connectivity

Premium platinum silver finish For a polished look that

For a polished look that complements the home and office In-Plane-Switching (IPS) Technology Experience superb visuals and rich colors including 99% sRGB color across a wide viewing angle

Enjoy superior sound with built-in 2 x 3W speakers

Optimize eye comfort with built-in ComfortView Plus that reduces harmful blue light emissions without sacrificing color performance

Adjust to your comfort

Tilt, swivel, pivot, and height adjustable

Easily charge and connect your laptop with USB-C connectivity and 65W of power delivery

3-sided Ultrathin bezels design for a seamless view

For leisure gaming -Smooth gameplay with AMD FreeSync[™], and up to 75Hz refresh rate.

Two USB ports with one quick-access port that supports up to 10W charging are always within your reach.



Environmentally conscious

Monitor is shipped Styrofoam-free, all-in packaging made of at least 75% recycled cardboard. The Dell Premium Panel Exchange allows a free panel replacement during the Limited Hardware Warranty* period even if only one bright pixel is found.

Click to explore: <u>Dell 27 USB-C Monitor – S2723HC</u>

*For copy of Ltd Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see //www.dell.com/warranty.

DELL MONITORS-S-series S2723HC

Viewable image size (diagonal)68.6 cm (27.0Active display area (horizontal x vertical)597.89 mm x (23.54" x 13.2Panel technologyIn-Plane SwiteMaximum preset resolutionFull HD (1920)Aspect ratio16.9Pixel pitch0.3114 mm xBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million cdContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), with 10W Pow worwstream FStand adjustabilityHeight adjustr Tilt -5° / 21°, 5Stand featuresBuilt-in cable of Power AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Me 0.3 W (StandtDimensions (HxWxD) Panel only Monitor had with stand(compressed/extended ht.)363.6 mm x 6 388.95 mm fWeight Panel only Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	36.31 mm ") ning (IPS); Anti-glare with 3H hardness x 1080) at 75Hz
Active display area (horizontal x vertical)597.89 mm x (23.54" x 13.2Panel technologyIn-Plane SwitchMaximum preset resolutionFull HD (1920)Aspect ratio16:9Pixel pitch0.3114 mm xBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million coContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, comforthDel Display Manager compatibilityYes, with DelilConnectivity1 x USB Type up to 65 W), with 10W Pow downstream pStand adjustabilityHeight adjust Tilt -5° / 21°, 3Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable loc 0.3 W (Off Mc 0.3 W (Standt)Power AC input voltage/frequency/current100 VAC to 22Power consumption (Operational)0.3 W (Off Mc 0.3 W (Standt)Dimensions (HxWxD) Panel only363.6 mm x 6 	36.31 mm ") ning (IPS); Anti-glare with 3H hardness x 1080) at 75Hz
Maximum preset resolutionFull HD (1920)Aspect ratio16:9Pixel pitch0.3114 mm xBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million cdContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSync™Yes, supportsTÜV-certifiedYes, ComforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), f with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5' / 21°, sStand featuresBuilt-in cable addition point Security lock slotPower AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Mc 0.3 W (Stand 21.33 mm (BcDimensions (HxWxD) Panel only 	x 1080) at 75Hz
Aspect ratio16:9Pixel pitch0.3114 mm xBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million cdContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSync™Yes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 3Stand featuresBuilt-in cableVESA mount compatibleYes (cable locPower AC input voltage/frequency/current100 VAC to 24Power consumption (Operational)0.3 W (Off Me 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 398.95 mm / 3Dimensions (HXWXD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 3Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	
Pixel pitch0.3114 mm xPixel pitch0.3114 mm xBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million cdContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), with 10W Pow downstream pStand adjustabilityHeight adjustr Titl -5° / 21°, 3Stand featuresBuilt-in cableVESA mount compatibleYes (cable loc 0.3 W (Off Me 0.3 W (StandtPower AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Me 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 398.95 mm / 3Dimensions (HXWXD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 3Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	.3114 mm
Brightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 million caContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSync™Yes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), divid 10W Pow odownstream pStand adjustabilityHeight adjust Tilt -5° / 21°, SStand featuresBuilt-in cableVESA mount compatibleYes, clobe doPower AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BcDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.2)	.3114 mm
Color gamut (typical)99% sRGBColor depth16.7 million colorContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSync™Yes, supportsTÜV-certifiedYes, ComfortDell Display Manager compatibilityYes, with DellConnectivity1 x USB Typeonectivity1 x USB TypeStand adjustabilityHeight adjustr Tilt -5° / 21°, SStand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 22Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BCDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 50Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 3.99 kg (19.2)	
Color depth16.7 million colorContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSync™Yes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, SStand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable loc Power AC input voltage/frequency/currentPower consumption (Operational)0.3 W (Off Me 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (Bo 0.3 W StandtDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 6 398.95 mm / 6	
Contrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Typegath adjustabilityYes, with DellStand adjustabilityHeight adjustrStand featuresBuilt-in cableVESA mount compatibleYes (cable locPower AC input voltage/frequency/current100 VAC to 22Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtDimensions (HxWxD) Panel only363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	
Typical viewing angles (vertical / horizontal)178° / 178°Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, comforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 5Stand featuresBuilt-in cableVESA mount compatibleYes (cable locPower AC input voltage/frequency/current100 VAC to 20Power consumption (Operational)0.3 W (Off Me 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BcDimensions (HxWxD) Panel only363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	ors
Response time (typical)4ms gray to gBacklightWhite LED edAudio Output2 x 3WAMD FreeSyncTMYes, supportsTÜV-certifiedYes, ComforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, \$Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BcDimensions (HxWxD) Panel only363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	
Backlight White LED ed Audio Output 2 x 3W AMD FreeSync™ Yes, supports TÜV-certified Yes, Comforth Dell Display Manager compatibility Yes, with Dell Connectivity 1 x USB Type up to 65 W), 4 with 10W Pow downstream p Stand adjustability Height adjustr Tilt -5° / 21°, 5 Stand features Built-in cable VESA mount compatible Yes (cable loc Power AC input voltage/frequency/current 100 VAC to 24 Power consumption (Operational) 0.3 W (Off Mo 0.3 W (Standt Border Width (Edge of Monitor to active area) 5.99/6.01/6.01 21.33 mm (Bo 0.3 W (Standt Border Width (Edge of Monitor to active area) Dimensions (HxWxD) Panel only 363.6 mm x 6 398.95 mm / 5 Panel only (for VESA) Monitor and cables with full packaging 4.65 kg (10.2 8.99 kg (19.8)	
Audio Output 2 x 3W AMD FreeSync™ Yes, supports TÜV-certified Yes, comforth Dell Display Manager compatibility Yes, with Dell Connectivity 1 x USB Type up to 65 W), 1 with 10W Pow downstream p Stand adjustability Stand features Built-in cable VESA mount compatible Yes, 100 mm Security lock slot Yes (cable loc) Power AC input voltage/frequency/current 100 VAC to 24 Power consumption (Operational) 0.3 W (Off Mo 0.3 W (Standth Stand tead with stand(compressed/extended ht.) 363.6 mm x 6 Meight Panel only 363.6 mm x 6 398.95 mm / 6 Monitor head with stand(compressed/extended ht.) 398.95 mm / 6 398.95 mm / 6	ay in extreme mode
AMD FreeSyncTMYes, supportsTÜV-certifiedYes, ComforthDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), 4 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 5Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable loc Power AC input voltage/frequency/currentPower consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (Bo 398.95 mm / 5Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 398.95 mm / 5	elight system
TÜV-certifiedYes, ComfortDell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, SStand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable loc Power AC input voltage/frequency/currentPower AC input voltage/frequency/current100 VAC to 20 0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BcDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5 99 kg (10.2 8.99 kg (1	
Dell Display Manager compatibilityYes, with DellConnectivity1 x USB Type up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 3Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable loc Power AC input voltage/frequency/currentPower AC input voltage/frequency/current100 VAC to 24 0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.04 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	AMD FreeSync [™] technology with refresh rate of 75Hz
Connectivity1 x USB Type up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 5Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 24Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	iew Plus ¹ with Flicker-free screen
up to 65 W), 1 with 10W Pow downstream pStand adjustabilityHeight adjustr Tilt -5° / 21°, 5Stand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 24Power consumption (Operational)0.3 W (Off Mo 0.3 W (Standt)Border Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	EasyArrange
Tilt -5° / 21°, SStand featuresBuilt-in cableVESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 20Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	C upstream port (Alternate mode with DisplayPort 1.2, Power Delivery x Super Speed USB 5 Gbps (USB 3.2 Gen1) Type-A downstream port er Charging, 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A ort, 1 x HDMI port (ver 1.4), HDCP 1.4, 1 x audio line-out port
VESA mount compatibleYes, 100 mmSecurity lock slotYes (cable locPowerAC input voltage/frequency/current100 VAC to 24Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	ent up to 110mm wivel -30° / 30°, Pivot <i>-</i> 90° / 90°
Security lock slotYes (cable locPower AC input voltage/frequency/current100 VAC to 24Power consumption (Operational)0.3 W (Off Mo 0.3 W (StandbBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) 	nanagement slot
Power AC input voltage/frequency/current 100 VAC to 24 Power consumption (Operational) 0.3 W (Off Mo 0.3 W (Standstandstandstandstandstandstandstands	100 mm
AC input voltage/frequency/current100 VAC to 2Power consumption (Operational)0.3 W (Off Mo 0.3 W (Stands)Border Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	sold separately)
Border Width (Edge of Monitor to active area)0.3 W (StandtBorder Width (Edge of Monitor to active area)5.99/6.01/6.01 21.33 mm (Bo 21.33 mm (BoDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm x 6 398.95 mm / 5Weight Panel only (for VESA) Monitor and cables with full packaging4.65 kg (10.2 8.99 kg (19.8)	0 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.7 A (maximum)
Dimensions (HxWxD) 363.6 mm x 6 Panel only 363.6 mm x 6 Monitor head with stand(compressed/extended ht.) 398.95 mm / 5 Weight 4.65 kg (10.2 Panel only (for VESA) 4.65 kg (10.2 Monitor and cables with full packaging 8.99 kg (19.8)	le) 17.3 W (On Mode) / Mode) 135 W (Max)
Panel only363.6 mm x 6Monitor head with stand(compressed/extended ht.)398.95 mm / 5Weight4.65 kg (10.2Panel only (for VESA)4.65 kg (10.2Monitor and cables with full packaging8.99 kg (19.8)	
Panel only (for VESA)4.65 kg (10.2Monitor and cables with full packaging8.99 kg (19.8	mm (Top/Left/Right) tom)
Environmental compliance ENERGY STA	
•	tom) 9.9 mm x 54.03 mm (14.32" x 24.01" x 2.13") 08.95 mm x 609.9 mm x 174.7 mm (15.71" / 20.04" x 24.01" x 6.88") lbs)
	tom) 9.9 mm x 54.03 mm (14.32" x 24.01" x 2.13") 08.95 mm x 609.9 mm x 174.7 mm (15.71" / 20.04" x 24.01" x 6.88") lbs)
What's Included Monitor panel. 3.2 Gen 1 cat Regulatory Int ¹ ComfortView Plus feature reduces blue light emission and optimizes eye comfort without color c ² Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion	tom) 9.9 mm x 54.03 mm (14.32" x 24.01" x 2.13") 08.95 mm x 609.9 mm x 174.7 mm (15.71" / 20.04" x 24.01" x 6.88") lbs) lbs) R certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding

DELL 27 USB-CMONITOR -

Technical specifications subject to change without prior notice.

Perduct availability variability varias by country. Please contact your Dell representative for more information. Copyright 2022 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden.